




# Product Specification

AU OPTRONICS CORPORATION

( ) Preliminary Specification

( V ) Final Specification

Module	15.4" WSXGA+ 16:10 Color TFT-LCD with LED Backlight design
Model Name	B154SW02 V3
Note (  )	LED Backlight <b>without</b> driving circuit design

Customer	Date
Checked & Approved by	Date
Note: This Specification is subject to change without notice.	

Approved by	Date
<u>CH Lin</u>	<u>07/26/2010</u>
Prepared by	Date
<u>Rod Lee</u>	<u>07/21/2010</u>
NBBU Marketing Division AU Optronics corporation	



# Product Specification

AU OPTRONICS CORPORATION

## Contents

<b>1. Handling Precautions .....</b>	<b>4</b>
<b>2. General Description .....</b>	<b>5</b>
2.1 General Specification .....	5
2.2 Optical Characteristics .....	6
<b>3. Functional Block Diagram .....</b>	<b>11</b>
<b>4. Absolute Maximum Ratings.....</b>	<b>12</b>
4.1 Absolute Ratings of TFT LCD Module .....	12
4.2 Absolute Ratings of Environment .....	12
<b>5. Electrical Characteristics.....</b>	<b>13</b>
5.1 TFT LCD Module.....	13
5.2 Backlight Unit .....	15
<b>6. Signal Interface Characteristic.....</b>	<b>16</b>
6.1 Pixel Format Image .....	16
6.2 The Input Data Format .....	17
6.3 Integration Interface Requirement.....	18
6.4 Interface Timing .....	20
<b>7. Panel Reliability Test .....</b>	<b>22</b>
7.1 Vibration Test .....	22
7.2 Shock Test .....	22
7.3 Reliability Test.....	22
<b>8. Mechanical Characteristics.....</b>	<b>23</b>
8.1 LCM Outline Dimension.....	23
<b>9. Shipping and Package .....</b>	<b>25</b>
9.1 Shipping Label Format.....	25
9.2 Carton Package.....	25
9.3 Shipping Package of Palletizing Sequence.....	25
<b>10. Appendix: EDID Description.....</b>	<b>26</b>

AU OPTRONICS CORPORATION

## Record of Revision

[illegible]



## Product Specification

AU OPTRONICS CORPORATION

### 1. Handling Precautions

- 1) Since front polarizer is easily damaged, pay attention not to scratch it.
- 2) Be sure to turn off power supply when inserting or disconnecting from input connector.
- 3) Wipe off water drop immediately. Long contact with water may cause discoloration or spots.
- 4) When the panel surface is soiled, wipe it with absorbent cotton or other soft cloth.
- 5) Since the panel is made of glass, it may break or crack if dropped or bumped on hard surface.
- 6) Since CMOS LSI is used in this module, take care of static electricity and insure human earth when handling.
- 7) Do not open nor modify the Module Assembly.
- 8) Do not press the reflector sheet at the back of the module to any directions.
- 9) At the insertion or removal of the Signal Interface Connector, be sure not to rotate nor tilt the Interface Connector of the TFT Module.
- 11) After installation of the TFT Module into an enclosure (Notebook PC Bezel, for example), do not twist nor bend the TFT Module even momentarily. At designing the enclosure, it should be taken into consideration that no bending/twisting forces are applied to the TFT Module from outside. Otherwise the TFT Module may be damaged.
- 12) Small amount of materials having no flammability grade is used in the LCD module. The LCD module should be supplied by power complied with requirements of Limited Power Source (IEC60950 or UL1950), or be applied exemption.
- 13) Disconnecting power supply before handling LCD modules, it can prevent electric shock, DO NOT TOUCH the electrode parts, cables, connectors and LED circuit part of TFT module that a LED light bar build in as a light source of back light unit. It can prevent electronic breakdown.



## Product Specification

AU OPTRONICS CORPORATION

### 2. General Description

B154SW02 V0 is a Color Active Matrix Liquid Crystal Display composed of a TFT LCD panel, a driver circuit, and LED backlight system. The screen format is intended to support the 16 :10 WSXGA+, 1680(H) x 1050(V) screen and 262k colors (RGB 6-bits data driver) without LED backlight driving circuit. All input signals are LVDS interface compatible.

B154SW02 V0 is designed for a display unit of notebook style personal computer and industrial machine.

#### 2.1 General Specification

The following items are characteristics summary on the table at 25 °C condition:

Items	Unit	Specifications			
Screen Diagonal	[mm]	390.8, 15.4"			
Active Area	[mm]	331.38 x 207.11			
Pixels H x V		1680 x 3(RGB) x 1050			
Pixel Pitch	[mm]	0.19725 x 0.19725			
Pixel Format		B.G.R. Vertical Stripe			
Display Mode		Normally White			
White Luminance (ILED=20mA) (Note: ILED is LED current)	[cd/m <sup>2</sup> ]	220 typ. (5 points average) 200 min. (5 points average)			
Luminance Uniformity		1.25 max. (5 points)			
Contrast Ratio		TBD			
Response Time	[ms]	16 typ / 25 Max			
Nominal Input Voltage VDD	[Volt]	+3.3 typ.			
Power Consumption	[Watt]	7			
Weight	[Grams]	455 max.			
Physical Size <b>Include bracket</b>	[mm]		Min.	Typ.	Max.
		Length	342.55	342.85	343.15
		Width	220.54	220.84	221.14
		Thickness	-	3.80	4.05
Electrical Interface		2 channel LVDS			
Glass Thickness	[mm]	0.5			
Surface Treatment		Anti-glare, Hardness 2H,			
Support Color		262K colors ( RGB 6-bit )			



## Product Specification

AU OPTRONICS CORPORATION

Temperature Range		
Operating	[°C]	0 to +50
Storage (Non-Operating)	[°C]	-25 to +65
RoHS Compliance		RoHS Compliance

## 2.2 Optical Characteristics

The optical characteristics are measured under stable conditions at 25°C (Room Temperature) :


Item		Symbol	Conditions	Min.	Typ.	Max.	Unit	Note
White Luminance I <sub>LED=20mA</sub>			5 points average	200	220	-	cd/m <sup>2</sup>	1, 4, 5.
Viewing Angle		$\theta_R$	Horizontal (Right) CR = 10 (Left)	32.5	35	-	degree	4, 9
		$\theta_L$		32.5	35	-		
		$\phi_H$	Vertical (Upper) CR = 10 (Lower)	27.5	30	-		
		$\phi_L$		27.5	30	-		
Luminance Uniformity		$\delta_{5P}$	5 Points	-	-	-		1, 3, 4
Luminance Uniformity		$\delta_{13P}$	13 Points	-	-	1.60		2, 3, 4
Contrast Ratio		CR		600	800	-		4, 6
Cross talk		%		-	-	4		4, 7
Response Time		T <sub>r</sub>	Rising	-	12	17	msec	4, 8
		T <sub>f</sub>	Falling	-	4	8		
		T <sub>RT</sub>	Rising + Falling	-	16	25		
Color / Chromaticity Coordinates	Red	R <sub>x</sub>	CIE 1931	0.615	0.645	0.675		4
		R <sub>y</sub>		0.305	0.335	0.365		
	Green	G <sub>x</sub>		0.285	0.315	0.345		
		G <sub>y</sub>		0.580	0.610	0.640		
	Blue	B <sub>x</sub>		0.110	0.140	0.170		
		B <sub>y</sub>		0.040	0.060	0.080		
	White	W <sub>x</sub>		0.300	0.313	0.326		
		W <sub>y</sub>		0.316	0.329	0.342		
	NTSC			%		67		




# Product Specification

AU OPTRONICS CORPORATION

**Note 1:** 5 points position (Ref: Active area)



**Note 2:** 13 points position (Ref: Active area)



**Note 3:** The luminance uniformity of 5 or 13 points is defined by dividing the maximum luminance values by the minimum test point luminance

$$\delta_{W5} = \frac{\text{Maximum Brightness of five points}}{\text{Minimum Brightness of five points}}$$

$$\delta_{W13} = \frac{\text{Maximum Brightness of thirteen points}}{\text{Minimum Brightness of thirteen points}}$$

**Note 4:** Measurement method

The LCD module should be stabilized at given temperature for 30 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting






## Product Specification

AU OPTRONICS CORPORATION

Backlight for 30 minutes in a stable, windless and dark room, and it should be measured in the center of screen.



**Note 5 :** Definition of Average Luminance of White ( $Y_L$ ):

Measure the luminance of gray level 63 at 5 points ,  $Y_L = [L(1) + L(2) + L(3) + L(4) + L(5)] / 5$

$L(x)$  is corresponding to the luminance of the point X at Figure in Note (1).

**Note 6 :** Definition of contrast ratio:

Contrast ratio is calculated with the following formula.

$$\text{Contrast ratio (CR)} = \frac{\text{Brightness on the "White" state}}{\text{Brightness on the "Black" state}}$$

**Note 7 :** Definition of Cross Talk (CT)

$$CT = |Y_B - Y_A| / Y_A \times 100 (\%)$$

Where

$Y_A$  = Luminance of measured location without gray level 0 pattern (cd/m<sup>2</sup>)


$Y_B$  = Luminance of measured location with gray level 0 pattern (cd/m<sup>2</sup>)






# Product Specification

AU OPTRONICS CORPORATION



**Note 8:** Definition of response time:

The output signals of BM-7 or equivalent are measured when the input signals are changed from "Black" to "White" (falling time) and from "White" to "Black" (rising time), respectively. The response time interval between the 10% and 90% of amplitudes. Refer to figure as below.






## Product Specification

AU OPTRONICS CORPORATION

### Note 9. Definition of viewing angle

Viewing angle is the measurement of contrast ratio  $\geq 10$ , at the screen center, over a  $180^\circ$  horizontal and  $180^\circ$  vertical range (off-normal viewing angles). The  $180^\circ$  viewing angle range is broken down as follows;  $90^\circ$  ( $\theta$ ) horizontal left and right and  $90^\circ$  ( $\Phi$ ) vertical, high (up) and low (down). The measurement direction is typically perpendicular to the display surface with the screen rotated about its center to develop the desired measurement viewing angle.






## Product Specification

AU OPTRONICS CORPORATION

### 3. Functional Block Diagram

The following diagram shows the functional block of the 15.4 inches wide Color TFT/LCD 40 Pin one channel Module





## Product Specification

AU OPTRONICS CORPORATION

### 4. Absolute Maximum Ratings

An absolute maximum rating of the module is as following:

#### 4.1 Absolute Ratings of TFT LCD Module

Item	Symbol	Min	Max	Unit	Conditions
Logic/LCD Drive Voltage	Vin	-0.3	+4.0	[Volt]	Note 1,2

#### 4.2 Absolute Ratings of Environment


Item	Symbol	Min	Max	Unit	Conditions
Operating Temperature	TOP	0	+50	[°C]	Note 4
Operation Humidity	HOP	5	95	[%RH]	Note 4
Storage Temperature	TST	-20	+60	[°C]	Note 4
Storage Humidity	HST	5	95	[%RH]	Note 4

Note 1: At Ta (25°C )

Note 2: Permanent damage to the device may occur if exceed maximum values

Note 3: LED specification refer to section 5.2

Note 4: For quality performance, please refer to AUO IIS (Incoming Inspection Standard).



Operating Range

Storage Range +



## Product Specification

AU OPTRONICS CORPORATION

### 5. Electrical Characteristics

#### 5.1 TFT LCD Module

##### 5.1.1 Power Specification



Input power specifications are as follows;

The power specification are measured under 25°C and frame frequency under 60Hz

Symble	Parameter	Min	Typ	Max	Units	Note
VDD	Logic/LCD Drive Voltage	3.0	3.3	3.6	[Volt]	
PDD	VDD Power	-	-	1.2	[Watt]	Note 1
IDD	IDD Current	-	363	400	[mA]	Note 1
IRush	Inrush Current	-	-	2000	[mA]	Note 2
VDDrp	Allowable Logic/LCD Drive Ripple Voltage	-	-	100	[mV] p-p	

Note 1 : Maximum Measurement Condition : Black Pattern at 3.3V driving voltage. ( $P_{\max} = V_{3.3} \times I_{\text{black}}$ )

Note 2 : Measure Condition



Vin rising time



## Product Specification

AU OPTRONICS CORPORATION


### 5.1.2 Signal Electrical Characteristics

Input signals shall be low or High-impedance state when VDD is off.

Signal electrical characteristics are as follows;

Parameter	Condition	Min	Max	Unit
$V_{th}$	Differential Input High Threshold ( $V_{cm}=+1.2V$ )	-	100	[mV]
$V_{tl}$	Differential Input Low Threshold ( $V_{cm}=+1.2V$ )	-100	-	[mV]
$V_{ID}$	Differential Input Voltage	100	600	[mV]
$V_{cm}$	Differential Input Common Mode Voltage	1.125	1.375	[V]

Note: LVDS Signal Waveform





## Product Specification

AU OPTRONICS CORPORATION

### 5.2 Backlight Unit

#### 5.2.1 LED characteristics

Parameter	Symbol	Min	Typ	Max	Units	Condition
Backlight Power Consumption	PLED	-	4.38	-	[Watt]	(Ta=25°C), Note 1 Vin =12V
LED Life-Time	N/A	10,000	-	-	Hour	(Ta=25°C), Note 2 If=20 mA
LED Forward Voltage	VF	2.8	-	3.0	[Volt]	(Ta=25°C) Note 1
LED Forward Current	IF		35		[mA]	(Ta=25°C) Note 1

**Note 1:** Calculator value for reference  $P_{LED} = V_F$  (Normal Distribution) \*  $I_F$  (Normal Distribution) / Efficiency

**Note 2:** The LED life-time define as the estimated time to 50% degradation of initial luminous.






# Product Specification

AU OPTRONICS CORPORATION

## 6. Signal Interface Characteristic

### 6.1 Pixel Format Image

Following figure shows the relationship of the input signals and LCD pixel format.






## Product Specification

AU OPTRONICS CORPORATION

### 6.2 The Input Data Format



Signal Name	Description	
R5 R4 R3 R2 R1 R0	Red Data 5 (MSB) Red Data 4 Red Data 3 Red Data 2 Red Data 1 Red Data 0 (LSB)	Red-pixel Data Each red pixel's brightness data consists of these 6 bits pixel data.
G5 G4 G3 G2 G1 G0	Green Data 5 (MSB) Green Data 4 Green Data 3 Green Data 2 Green Data 1 Green Data 0 (LSB)	Green-pixel Data Each green pixel's brightness data consists of these 6 bits pixel data.
B5 B4 B3 B2 B1 B0	Blue Data 5 (MSB) Blue Data 4 Blue Data 3 Blue Data 2 Blue Data 1 Blue Data 0 (LSB)	Blue-pixel Data Each blue pixel's brightness data consists of these 6 bits pixel data.
RxCLKIN	Data Clock	The signal is used to strobe the pixel data and DE signals. All pixel data shall be valid at the falling edge when the DE signal is high.
DE	Display Timing	This signal is strobed at the falling edge of RxCLKIN. When the signal is high, the pixel data shall be valid to be displayed.
VS	Vertical Sync	The signal is synchronized to RxCLKIN .
HS	Horizontal Sync	The signal is synchronized to RxCLKIN .

Note: Output signals from any system shall be low or High-impedance state when VDD is off.



## Product Specification

AU OPTRONICS CORPORATION

### 6.3 Integration Interface Requirement

#### 6.3.1 Connector Description

Physical interface is described as for the connector on module.

These connectors are capable of accommodating the following signals and will be following components.

Connector Name / Designation	For Signal Connector
Manufacturer	IPEX or compatible
Type / Part Number	IPEX 20474-040E-12 or compatible
Mating Housing/Part Number	IPEX 20472-040T or compatible

#### 6.3.2 Pin Assignment

LVDS is a differential signal technology for LCD interface and high speed data transfer device.


PIN #	SIGNAL NAME	DESCRIPTION
1	GND	GND
2	VDD	Power Supply, 3.3 V (typical)
3	VDD	Power Supply, 3.3 V (typical)
4	V EEDID	DDC 3.3V power
5	Vsync	Vsync
6	Clk EEDID	DDC Clock
7	DATA EEDID	DDC Data
8	Odd_Rin0-	- LVDS differential data input (R0-R5, G0) (odd pixels)
9	Odd_Rin0+	+ LVDS differential data input (R0-R5, G0) (odd pixels)
10	VSS	Ground – Shield
11	Odd_Rin1-	- LVDS differential data input (G1-G5, B0-B1) (odd pixels)
12	Odd_Rin1+	+ LVDS differential data input (G1-G5, B0-B1) (odd pixels)
13	VSS	Ground – Shield
14	Odd_Rin2-	- LVDS differential data input (B2-B5, HS, VS, DE) (odd pixels)
15	Odd_Rin2+	+ LVDS differential data input (B2-B5, HS, VS, DE) (odd pixels)
16	VSS	Ground – Shield
17	Odd_ClkIN-	- LVDS differential clock input (odd pixels)
18	Odd_ClkIN+	+ LVDS differential clock input (odd pixels)
19	VSS	Ground – Shield
20	Even_Rin0-	- LVDS differential data input (R0-R5, G0) (even pixels)
21	Even_Rin0+	+ LVDS differential data input (R0-R5, G0) (even pixels)
22	VSS	Ground – Shield
23	Even_Rin1-	- LVDS differential data input (G1-G5, B0-B1) (even pixels)



## Product Specification



AU OPTRONICS CORPORATION

24	Even_Rin1+	+ LVDS differential data input (G1-G5, B0-B1) (even pixels)
25	VSS	Ground – Shield
26	Even_Rin2-	- LVDS differential data input (B2-B5, HS, VS, DE) (even pixels)
27	Even_Rin2+	+ LVDS differential data input (B2-B5, HS, VS, DE) (even pixels)
28	VSS	Ground – Shield
29	Even_ClkIN-	- LVDS differential clock input (even pixels)
30	Even_ClkIN+	+ LVDS differential clock input (even pixels)
31	VDC1	LED Cathode (Negative)
32	VDC2	LED Cathode (Negative)
33	VDC3	LED Cathode (Negative)
34	VDC4	LED Cathode (Negative)
35	VDC5	LED Cathode (Negative)
36	VDC6	LED Cathode (Negative)
37	NC	NC
38	VDDLED	7.5V – 21V LED power
39	VDDLED	7.5V – 21V LED power
40	VDDLED	7.5V – 21V LED power



**Signal Pin 1**

**Signal Pin 40**





## Product Specification

AU OPTRONICS CORPORATION

Note1: Input signals shall be low or High-impedance state when VDD is off.

### 6.4 Interface Timing


#### 6.4.1 Timing Characteristics

Basically, interface timings should match the 1680x1050/60Hz manufacturing guide line timing.

Parameter		Symbol	Min.	Typ.	Max.	Unit
Frame Rate		-	-	60	-	Hz
Clock frequency		1/ T <sub>Clock</sub>	-	119.3	-	MHz
Vertical Section	Period	T <sub>V</sub>	-	1080	-	T <sub>Line</sub>
	Active	T <sub>VD</sub>	1050			
	Blanking	T <sub>VB</sub>	-	30	-	
Horizontal Section	Period	T <sub>H</sub>	-	1840	-	T <sub>Clock</sub>
	Active	T <sub>HD</sub>	1680			
	Blanking	T <sub>HB</sub>	-	160	-	

Note : DE mode only

#### 6.4.2 Timing diagram






## Product Specification

AU OPTRONICS CORPORATION

### 6.5 Power ON/OFF Sequence

Power on/off sequence is as follows. Interface signals and LED on/off sequence are also shown in the chart. Signals from any system shall be Hi-Z state or low level when VDD is off



Power Sequence Timing

Parameter	Value			Units
	Min.	Typ.	Max.	
T1	0.5	-	10	ms
T2	0	-	50	
T3	0	-	50	
T4	400	-	-	
T5	200	-	-	
T6	200	-	-	
T7	0	-	10	



## Product Specification

AU OPTRONICS CORPORATION

### 7. Panel Reliability Test

#### 7.1 Vibration Test

**Test Spec:**

- Test method: Non-Operation
- Acceleration: 3.0 G
- Frequency: 5 - 150Hz Random
- Sweep: 30 Minutes each Axis (X, Y, Z)

#### 7.2 Shock Test

**Test Spec:**

- Test method: Non-Operation
- Acceleration: 220 G , Half sine wave
- Active time: 2 ms
- Pulse: X,Y,Z .one time for each side

#### 7.3 Reliability Test

Items	Required Condition	Note
Temperature Humidity Bias	Ta= 40°C, 90%RH, 300h	
High Temperature Operation	Ta= 50°C, Dry, 300h	
Low Temperature Operation	Ta= 0°C, 300h	
High Temperature Storage	Ta= 65°C, 300h	
Low Temperature Storage	Ta= -25°C, 300h	
Thermal Shock Test	Ta=-25°C to 65°C, Duration at 30 min, 100 cycles	
ESD	Contact : ±8 KV Air : ±15 KV	Note 1


**Note1:** According to EN 61000-4-2 , ESD class B: Some performance degradation allowed. No data lost  
Self-recoverable. No hardware failures.


**Remark:** MTBF (Excluding the LED): 30,000 hours with a confidence level 90%



## 8. Mechanical Characteristics

### 8.1 LCM Outline Dimension





Back View

## 9. Shipping and Package

### 9.1 Shipping Label Format

B154SW02 V3


Size: 9mm x 90mm



### 9.2 Carton Package

The outside dimension of carton is 455 (L)mm x 380 (W)mm x 355 (H)mm

### 9.3 Shipping Package of Palletizing Sequence





## 10. Appendix: EDID Description

		Release time		2009/3/30 14:49
FUNCTION	B154SW02 V1	Value	Value	Note
Header	HEX	BIN	DEC	
	00	00000000	0	
	FF	11111111	255	
	FF	11111111	255	
	FF	11111111	255	
	FF	11111111	255	
	FF	11111111	255	
	FF	11111111	255	
	00	00000000	0	
EISA Manuf. Code LSB	06	00000110	6	APP9CB9 0 00001(A) 10000(P) 10000(P) 9CB9 (apple assigned code)
Compressed ASCII	10	00010000	16	
Product Code	89	10111000	185	
hex. LSB first	9C	10011100	156	
32-bit ser #	01	00000001	1	unused
	01	00000001	1	
	01	00000001	1	
	01	00000001	1	
Week of manufacture	17	00010111	23	Week 31
Year of manufacture	13	00010011	19	19(2009-1990-19)
EDID Structure Ver.	01	00000001	1	
EDID revision #	03	00000011	3	
Video input definition	80	10000000	128	Digital Input
Max H image size	21	00100001	33	33.1cm
Max V image size	15	00010101	21	20.7cm
Display Gamma	78	01111000	120	Gamma 2.2
Feature support	0A	00001010	10	no DPMS,Active off,RGB color
Red/green low bits	F5	11110101	245	
Blue/white low bits	95	10010101	149	
Red x/ high bits	A3	10100011	163	Rx=0.640
Red y	55	01010101	85	Ry=0.340
Green x	4F	01001111	79	Gx=0.310
Green y	9C	10011100	156	Gy=0.610
Blue x	26	00100110	38	Bx=0.150
Blue y	0F	00001111	15	By=0.660
White x	50	01010000	80	Wx=0.313
White y	54	01010100	84	Wy=0.329
Established timing 1	00	00000000	0	unused
Established timing 2	00	00000000	0	
Manufacturer's Timing	00	00000000	0	
Standard timing #1	01	00000001	1	
	01	00000001	1	
Standard timing #2	01	00000001	1	
	01	00000001	1	
Standard timing #3	01	00000001	1	
	01	00000001	1	
Standard timing #4	01	00000001	1	
	01	00000001	1	
Standard timing #5	01	00000001	1	
	01	00000001	1	
Standard timing #6	01	00000001	1	
	01	00000001	1	
Standard timing #7	01	00000001	1	
	01	00000001	1	
Standard timing #8	01	00000001	1	
	01	00000001	1	
Pixel Clock/10,000 (LSB)	9A	10011010	154	Timing Descriptor #1
Pixel Clock/10,000 (MSB)	2E	00101110	46	1680x1050 @60_mode:pixel clock=119.3MHz
Horiz. Active pixels(Lower 8 bits)	90	10010000	144	Horiz active=1680 pixels
Horiz. Blanking (Lower 8 bits)	A0	10100000	160	Horiz blanking=160 pixels
Horiz. Active pixels(Horiz. Blanking (Upper:4 bits)	60	01100000	96	
	1A	00011010	26	Vertical active=1050 lines
	1E	00011110	30	Vertical blanking=30 lines
Vert. Active pixels:Vert. Blanking (Upper:4 bits)	40	01000000	64	
	30	00110000	48	Horiz sync. Offset=48 pixels
Vert. Sync. Offset=xx lines, Sync Width=xx lines	20	00100000	32	Horiz sync. Pulse Width=32 pixels
Horz. Ver. Sync/Width (Upper 2 bits)	36	00110110	54	Verti sync. Offset=3 lines,Sync Width=6 lines
	00	00000000	0	
Horiz. Image size (Lower 8 bits)	4B	01001011	75	Hori image size= 331 mm
Vert. Image size (Lower 8 bits)	CF	11001111	207	Verti image size = 207mm
Horiz. Image size : Vert. Image size (Upper 4 bits)	10	00010000	16	
	00	00000000	0	Horizontal Border = 0
	00	00000000	0	Vertical Border = 0
	18	00011000	24	
Detailed timing/monitor descriptor #2	00	00000000	0	ASCII Data String:B154SW02 V1
	00	00000000	0	
	00	00000000	0	
	01	00000001	1	For apple
Version	00	00000000	0	For apple
Apple edid signature	06	00000110	6	For apple
Apple edid signature	10	00010000	16	For apple
Link Type (LVDS Link,MSB justified)	30	00110000	48	For apple
Pixel and link component format (6-bit panel interface)	00	00000000	0	For apple
Panel features (No inverter)	00	00000000	0	For apple
	00	00000000	0	
	00	00000000	0	
	00	00000000	0	
	00	00000000	0	
	0A	00001010	10	
	20	00100000	32	
Detailed timing/monitor descriptor #3	00	00000000	0	ASCII Data String:B154SW02 V1
	00	00000000	0	
	FE	11111110	254	
	00	00000000	0	
	42	01000010	66	B
	31	00110001	49	1
	35	00110101	53	5
	34	00110100	52	4
	53	01010011	83	S
	57	01010111	87	W
	30	00110000	48	0
	32	00110010	50	2
	20	00100000	32	
	56	01010110	86	V
	31	00110000	49	1
	0A	00001010	10	
	20	00100000	32	
Detailed timing/monitor descriptor #4	00	00000000	0	Monitor Name: Color LCD
	00	00000000	0	
	00	00000000	0	
	FE	11111110	254	
	00	00000000	0	
	43	01000011	67	C
	6F	01101111	111	e
	6C	01101100	108	l
	6F	01101111	111	e
	72	01110010	114	r
	20	00100000	32	
	4C	01001100	76	L
	43	01000011	67	C
	44	01000100	68	D
	0A	00001010	10	
	20	00100000	32	
	20	00100000	32	
	20	00100000	32	
Extension Flag	00	00000000	0	
Checksum	C1	01111110	193	
SUM		6912		
SUM to HEX		1B00		
Check		00		